

STANDARD FEATURES AND OPTIONS – RAM PICKUP

All Dodge Ram Pickup models include:

- Air Bags*** – Next-Generation, multistage, driver and front-passenger (with front-passenger air bag on/off switch on Regular Cab)
- Air Conditioning** – CFC-free refrigerant (Dual-Zone Temperature Control on Laramie)
- Alternator** – 136-amp
- Axle Ratio** – 3.55 (1500) and 3.92 (on all 1500 Quad Cab® 4X4 models)
– 3.73 (2500/3500) and 4.10 (3500 with Dual Rear Wheel and 5.7-litre V8)
- Brake-Park Interlock** – Included with automatic transmission
- Bumpers** – Bright, front and rear with rear step pads
- Cargo Box** – Includes stake pockets, cargo tie-down cleats, two-tier loading and bulkhead provision
- Child-Seat Anchor System (LATCH)** – Lower Anchors and upper Tether anchors for CHild seats
- Cup Holders** – Front – Lower instrument panel-mounted (2) (with automatic transmission)
– Floor console-mounted (2) (with manual transmission)
– Rear – Floor-mounted (2) on SLT and Laramie (Quad Cab®)
- Engine Block Heater**
- Exhaust** – Stainless steel (gas models)

- Fascia** – Upper, Grey (ST)
– Upper, body-colour (SLT and Laramie)
- Fuel Tank** – Short box – 98-litre (21 Imp. gal.) (1500)
– 128-litre (28 Imp. gal.) (2500/3500)
– Long box – 132-litre (29 Imp. gal.)
- Grille** – Bright (ST and SLT), Dark Grey (2500/3500 ST) and Bright, with Bright billets (Laramie)
- Horn** – Dual-note
- Instrument Cluster** – Gauges include speedometer, tachometer, fuel, oil pressure, coolant temperature, and voltage. Indicator lamps include air bags, anti-lock brakes (ABS), check engine, door ajar, lamp out, low fuel, low washer fluid, seat belt reminder, transmission temperature, Tow mode (automatic transmission) and 4X4 if equipped
- Insulation** – Dash Liner
- Lighter** – Cigar
- Lighting** – Interior – Dome lamp
– Glove box lamp (SLT and Laramie)
– Exterior – Cargo lamp and centre high-mounted stop light
- Meter** – Engine hours (located in instrument cluster and read through the odometer)
- Power Outlet** – 12-volt auxiliary (located in lower instrument panel)
- Seat Belts** – Height-adjustable shoulder (driver and outboard front passenger), shoulder/lap belt, for centre front passenger (Regular Cab),

- rear outboards and centre rear passenger (Quad Cab®) and a lap belt for centre front passenger (Quad Cab®)
- Sentry Key™ Engine Immobilizer** – Theft deterrent system with two encoded keys
- Side-Impact Intrusion Protection** – Includes steel side-guard door beams and structural body reinforcements
- Spare Tire** – Full-size
- Stabilizer Bar** – Front
- Steering** – Power-assisted, rack-and-pinion (1500 and 4X2 2500/3500)
– Power-assisted, precision recirculating-ball (4X4 2500/3500)
- Steering Column** – Tilt
- Suspension** – Heavy-duty gas-charged front-and-rear shock absorbers and front stabilizer bar
– Front – Independent coil spring (4X2), independent torsion bar (4X4 1500), solid live axle with coil springs (4X4 2500/3500)
– Rear – Longitudinal leaf springs
- Tailgate** – Removable with quick-release latches
- Wheels and Tires** – 17-inch
- Winch** – Tire carrier
- Window** – Tinted Glass
– Rear cab, fixed (ST and SLT)
- Wiper System** – Windshield, variable intermittent
- Wiring** – Trailer-tow with four-pin connector

DODGE RAM – 1500, 2500, 3500 POWERTRAIN AVAILABILITY

	PACKAGES								
	1500			2500			3500		
	ST	SLT	Laramie	ST	SLT	Laramie	ST	SLT	Laramie
Engine									
3.7L (226 CID) Magnum® V6									
3.7L (226 CID) Magnum® V6									
4.7L (287 CID) Magnum® V8									
4.7L (287 CID) Magnum® V8									
5.7L (345 CID) HEMI® Magnum® V8									
5.7L (345 CID) HEMI® Magnum® V8									
5.7L (345 CID) HEMI® Magnum® V8				25A	25G	25H	25A	25G	25H
5.7L (345 CID) HEMI® Magnum® V8				26A	26G	26H	26A	26G	26H
5.9L (359 CID) Cummins® H.O. Turbo Diesel I-6				2BA	2BG	2BH	2BA	2BG	2BH
5.9L (359 CID) Cummins® H.O. Turbo Diesel I-6				2UA	2UG	2UH	2UA	2UG	2UH
Air Bags* – Supplemental side-curtain, front-and-rear outboard occupants	0	0	0	0	0	0	0	0	0
Axles – With anti-spin rear differential (specific ratios only)	0	0	0	0	0	0	0	0	0
Battery – 600-amp, Maintenance-Free	■	■	■	■	■	■	■	■	■
– 750-amp Maintenance-Free (included with Snow Plow Prep Group, Trailer-Tow Group and 5.9L Turbo Diesel engine)	P	P	P	P	P	P	P	P	P
Bedliner – Box-under-rail type	0	0	0	0	0	0	0	0	0
Brakes – Power-assisted 4-wheel disc with rear-wheel anti-lock (ABS)	■	■							
– Power-assisted 4-wheel disc with 4-wheel anti-lock (ABS)	0	0	■	■	■	■	■	■	■
Console – Overhead, with trip computer		■			■			■	
– Overhead, with trip computer and HomeLink® Universal Transceiver ⁽²⁾			■		■				■
Door Locks – Power		■	■		■	■		■	■
Defogger/Defroster – Rear window (requires fixed privacy glass)		0	0		0	0		0	0
Engine Cooling – Heavy-duty (requires automatic transmission 1500) (included in 1500 Trailer-Tow Group and 1500 Off-Road Group) (not available with 3.7L V6 engine)	O/P	O/P	O/P	■	■	■	■	■	■
Floor Covering – Heavy-duty vinyl	■			■			■		
– Carpeting, front-seat area	0	■	■	0	■	■	0	■	■
Floor Mats – Front, carpeted		■	■		■	■		■	■
Fog Lamps – Included with Sport Appearance Group and Off-Road Group		O/P	■		O/P	■		O/P	■
Fuel Tank – 128-litre (available with Quad Cab® short box)	0	0	0						
Grille – Chrome surround and cross bars with black honeycomb	■	■		0	■		0	■	
– Dark Grey surround and cross bars with black honeycomb (included with 1500 Work Special Group)	P			■			■		
– Body-colour surround and cross bars, chrome billets (included in Sport Appearance Group)		P	P		P	P		P	P
– Chrome surround, cross bars and chrome billets			■			■			■

(Cont'd)	PACKAGES								
	1500			2500			3500		
	ST	SLT	Laramie	ST	SLT	Laramie	ST	SLT	Laramie
Light Group – Includes sun visors with illuminated vanity mirrors, auto-dim rearview mirror (SLT), ash tray lamp, front dome light with on/off switch and underhood lamp		0	■		0	■		0	■
Lighting – Exterior – Cab clearance lamps (5, roof-mounted)				0	0	0	■	■	■
– Box clearance and rear fender lamps (not available with Single Rear Wheel Group or short box)							■	■	■
Mirrors – Exterior – Dual, 6x9-inch, manual, Black (3500 Single Rear Wheel)	■			■			■		
– Dual, 6x9-inch, power, heated, folding (3500 Single Rear Wheel)		■	■		■	■		■	■
– Dual, 6x9-inch, manual, Black (3500 Dual Rear Wheel)							■		
– Dual, 6x9-inch, power, heated, Black (3500 Dual Rear Wheel)								■	■
– Dual, 7x10-inch, trailer-tow, folding	0			0			0		
– Dual, 7x10-inch, trailer-tow, power, folding		0	0		0	0		0	0
– Interior – Rearview, automatic dimming day/night (included in Light Group)		0/P	■		0/P	■		0/P	■
Mouldings – Bodyside, (Black on ST and SLT, Chrome on Laramie and body-colour with Sport Appearance Group)	0	0/P	■	0	0/P	■	0	0/P	■
Off-Road Group – (4x4 only) Includes 3.92 differential (1500) and 4.10 differential (2500/3500) both with anti-spin, heavy-duty engine cooling (1500), transfer case skid plate, front suspension skid plate (1500), LT275/70R17 OWL All-Terrain tires (1500), LT265/70R17E OWL On/Off-Road tires (2500/3500), 17x8-inch cast aluminum wheels (1500), trim level wheels (2500/3500), Off-Road decals, tow hooks, fog lamps and front-and-rear shocks painted red (varies by available model)		0			0			0	
Paint – Two-tone treatment, lower break; includes secondary colour on lower break (Bright Silver Metallic) (not available with 3500 Regular Cab 4x2/4x4)	0	0	0	0	0	0	0	0	0
Pedals – Power adjustable		0	■		0	■		0	■
Pickup Box Delete – Includes spare tire delete (requires Single Rear Wheel Group)				0	0	0	0	0	0
– Add full-size spare tire (requires Pickup Box Delete)				0	0	0	0	0	0
Power Outlet – 12-volt auxiliary located in the centre armrest/business console (requires premium cloth-faced or leather-faced seating)		0	■		0	■		0	■
Protection Group – (4x4 only) includes front suspension skid plate (1500), transfer case skid plate, and tow hooks	0	0	0	0	0	0	0	0	0
Rear Wheel Configuration – Single Rear Wheel	■	■	■	■	■	■	0 ⁽³⁾	0 ⁽³⁾	0 ⁽³⁾
– Dual Rear Wheel “Dually”							■ ⁽⁴⁾	■ ⁽⁴⁾	■ ⁽⁴⁾
Remote Keyless Entry – Controls for power door locks, illuminated entry system, panic alarm, and two key fobs		■	■		■	■		■	■
Seats – All seats and interiors are available in Taupe or Dark Slate Grey									
– Heavy-duty vinyl 40/20/40 front split-bench with adjustable front-and-rear head restraints for outboard seating positions, folding seatback, driver and front-passenger recliners and folding centre armrest (Quad Cab® includes vinyl folding rear seat)	■			■			■		
– Deluxe cloth-faced 40/20/40 front split-bench with adjustable front-and-rear head restraints for outboard seating positions, folding seatback, driver and front-passenger recliners and folding centre armrest (Quad Cab® includes deluxe cloth-faced folding rear seat)	0	■		0	■		0	■	
– Premium cloth-faced 40/20/40 front split-bench with adjustable front-and-rear head restraints for outboard seating positions, folding seatback, driver and passenger recliners (available centre armrest/business console and power driver seat) (Quad Cab® includes premium cloth-faced 60/40 split-folding rear seat)		0			0			0	
– Leather-faced 40/20/40 front split-bench with adjustable front-and-rear head restraints for outboard seating positions, folding seatback, driver and passenger recliners and folding centre armrest/business console (Quad Cab® includes leather-faced 60/40 split-folding rear seat) (Preferred Suede™ inset on Laramie) (not available with Regular Cab SLT model)		0	■		0	■		0	■
– Heated, driver and front-passenger			0			0			0
– Power, driver's seat (available with premium cloth-faced or leather-faced seating)		0	P		0	P		0	P
– Power, driver and front-passenger seats (Quad Cab®)			■			■			■
Security Group – Includes security alarm		0	■		0	■		0	■
Shield – Front hood protection	0	0	0	0	0	0	0	0	0
Skid Plate (4x4 only) – Front suspension, included with Protection Group and Off-Road Group	P	P	P	P	P	P	P	P	P
– Transfer case, included with Protection Group, Snow Plow Prep Group and Off-Road Group	P	P	P	P	P	P	P	P	P
Snow Plow Prep Group ⁽⁵⁾ – (4x4 only) Includes transfer case skid plate, 160-amp alternator and 750-amp Maintenance-Free battery. Varies by available model. See your retailer for complete details and availability				0	0	0	0	0	0
Sound System – AM/FM stereo with cassette player (CD changer controls) and 4 speakers	■			■			■		
– AM/FM stereo with CD player (CD changer controls) and 4 speakers	0	■		0	■		0	■	
– AM/FM stereo with cassette/CD player with Infinity® premium sound system		0	■		0	■		0	■
– AM/FM stereo with 6-disc in-radio CD changer with Infinity® premium sound system		0	0		0	0		0	0
– Speakers – 4, including full-range 6X9-inch in front doors and 5 1/4-inch full-range on “B” pillars in Regular Cab and rear doors in Quad Cab®	■	■		■	■		■	■	
– Infinity® Premium Sound System – 11 speakers in 7 locations with a 240-watt digital amplifier. Speakers include 2½-inch in the centre of the instrument panel, 3½-inch left-and-right side instrument panel, 6x9-inch woofer in front doors, 5½-inch coaxial on “B” pillars in Regular Cab and rear doors in Quad Cab®		P	■		P	■		P	■
– Audio Controls – Steering wheel-mounted (requires leather-wrapped steering wheel and premium sound system)		0	■		0	■		0	■
Speed Control	0	■	■	0	■	■	0	■	■

STANDARD FEATURES AND OPTIONS – RAM PICKUP

(Cont'd)	PACKAGES								
	1500			2500			3500		
	ST	SLT	Laramie	ST	SLT	Laramie	ST	SLT	Laramie
Sport Appearance Group – Includes front fascia, grille, bodyside mouldings, and rear bumper with rear step pads in body colour, fog lamps and aluminum wheels on Single Rear Wheel models (available in select colours)		O	O		O	O		O	O
Steering Wheel – Leather-wrapped (included with leather-faced seating)		O/P	■		O/P	■		O/P	■
Storage – Behind seat tray (Regular Cab); steel bins under rear seat (Quad Cab®)	■	■	■	■	■	■	■	■	■
– Front seat centre in-cushion available with Premium cloth-faced and leather-faced seating		O	■		O	■		O	■
– 60/40 rear fold-flat steel floor covering storage bins under rear seat (Quad Cab®) (available with Premium cloth-faced seats and included with SLT leather-faced seats)		O/P	■		O/P	■		O/P	■
Sun Visor – Driver and front-passenger with right-side mirror		■	■		■	■		■	■
– Driver and front-passenger with illuminated vanity mirrors (included with Light Group)		P	P		P	P		P	P
Tires – See your retailer for complete details and availability									
Tow Hooks – (4x4) Included with Protection Group and Off-Road Group	P	P	O/P	P	P	O/P	P	P	O/P
– (4x2) Not available with 3.7L V6 engine on 1500	O	O	O	O	O	O	O	O	O
Trailer-Tow Group ⁽⁶⁾ – Includes heavy-duty engine cooling with automatic transmission on 1500, 750-amp battery, Class IV hitch receiver and a 7-pin wiring harness	O	O	O	O	O	O	O	O	O
Transfer Case – (4x4 only) – Manual shift – Two-range part-time shift-on-the-fly, floor-mounted shifter	■	■		■	■		■	■	
– Electronic shift – Two-range part-time shift-on-the-fly, instrument panel control (not available with 1500 4.7L V8 engine with manual transmission)		O	■		O	■		O	■
– Full-time shift-on-the-fly, instrument panel control (requires 5-speed automatic transmission)		O	O						
Tubular Side-Steps [†] – Chrome	O	O	O	O	O	O	O	O	O
Wheels – 17x7-inch Steel, Argent	■								
– 17x8-inch Steel, chrome-clad	O	■	■						
– 17x8-inch Cast aluminum, chrome centre cap (included with Sport Appearance Group)		O/P	P						
– 17x8-inch Aluminum (included with Off-Road Group)		P							
– 20x9-inch Chrome-clad cast aluminum with chrome centre		O ⁽⁷⁾	O ⁽⁷⁾						
– 20x9-inch Polished cast aluminum with chrome centre		O ⁽⁷⁾							
– 17x7.5-inch Styled steel, painted				■			■ ⁽⁸⁾		
– 17x8-inch Steel, chrome-clad					■	O		■ ⁽⁸⁾	O ⁽⁸⁾
– 17x8-inch Cast aluminum (included with Sport Appearance Group) (SLT model)					O/P	■		O/P ⁽⁸⁾	■ ⁽⁸⁾
– 17x6-inch Steel, Argent							■ ⁽⁹⁾		
– 17x6-inch Steel with chrome wheel skin							O ⁽⁹⁾	■ ⁽⁹⁾	■ ⁽⁹⁾
Windows – Power (with driver's side, one-touch-down feature)		■	■		■	■		■	■
– Rear, sliding	O	O	■	O	O	■	O	O	■
Work Special Group – Includes front fascia, rear bumper with rear step pads and grille in Dark Grey (not available with 5.7L V8 engine)	O								

■ – Included P – Packaged with optional group or feature noted O – Optional O/P – Item is a freestanding option and is also included in a group CID – Cubic Inch Displacement SOHC – Single Overhead Cam H.O. – High Output

*Certified to federal regulations that allow less forceful air bags. Always use seat belts. For Regular Cab, children 12 and under should only be in the front seat with the passenger air bag switch turned off, correctly using an infant or child restraint system, or the seat belt properly positioned for the child's age and size. For Quad Cab®, children 12 and under should always be in a back seat correctly using an infant or child restraint system, or the seat belt properly positioned for the child's age and size. ⁽¹⁾Optional ratios available in combination with anti-spin differential. ⁽²⁾May not be compatible with all garage door openers. See retailer for details. ⁽³⁾Optional on Quad Cab® with diesel engine and standard on Quad Cab® short box with diesel engine. ⁽⁴⁾Single Rear Wheel standard on Quad Cab® short box models with diesel engine. ⁽⁵⁾With group shown, must have extra cost Trailer-Tow Group. Available with certain models only. See your retailer for complete details. ⁽⁶⁾Dodge Trucks used to tow trailers over 905 kg (2000 lb.) loaded weight must be equipped with Trailer-Tow Group, and trailers over 454 kg (1000 lb.) loaded weight must have their own brakes. Other restrictions may apply. For more information on trailer towing, visit dodge.ca or see your Dodge retailer. ⁽⁷⁾Short box only and requires 3.92 axle ratio. ⁽⁸⁾Single Rear Wheel. ⁽⁹⁾Dual Rear Wheel. [†]Late Availability.

ENGINE SPECIFICATIONS	Valve/Induction Systems	Maximum Horsepower	Maximum Torque
3.7L (226 CID) Magnum® V6 ⁽¹⁾	12-valve SOHC, SMPI	160 kW (215 bhp) @ 5200	319 N·m (235 lb-ft) @ 4000
4.7L (287 CID) Magnum® V8	16-valve SOHC, SMPI	175 kW (235 bhp) @ 4600	400 N·m (295 lb-ft) @ 3600
5.7L (345 CID) HEMI® Magnum® V8	16-valve OHV, SMPI	257 kW (345 bhp) ⁽²⁾ @ 5400	509 N·m (375 lb-ft) @ 4200
8.3L (505 CID) Viper V10 ⁽³⁾	20-valve OHV, SMPI	372 kW (500 bhp) @ 5600	712 N·m (525 lb-ft) @ 4200
5.9L (359 CID) Cummins® H.O. Turbo Diesel I-6 ⁽⁴⁾	24-valve OHV	227 kW (305 bhp) @ 2900	753 N·m (555 lb-ft) @ 1400
5.9L (359 CID) H.O. Cummins® 600 Turbo Diesel I-6 ⁽⁵⁾	24-valve OHV	242 kW (325 bhp) @ 2900	813 N·m (600 lb-ft) @ 1600

CID – Cubic Inch Displacement SOHC – Single Overhead Camshaft OHV – Overhead Valve SMPI – Sequential Multi-Point Fuel Injection H.O. – High-Output ⁽¹⁾Available on 1500 ST models (4x2) (Not available on 1500 Quad Cab® with long box) ⁽²⁾330 horsepower @ 4800 rpm on 3500 models. ⁽³⁾Ram SRT-10 only. ⁽⁴⁾Available until the end of December 2003. ⁽⁵⁾Available January 2004.

EXTERIOR DIMENSIONS*	REGULAR CAB 4x2/4x4		QUAD CAB® 4x2/4x4	
	1500			
	Short Box	Long Box	Short Box	Long Box
Wheelbase	3061 (120.5)	3569 (140.5)	3569 (140.5)	4077 (160.5)
Box Length – m (ft. in.)	1.9 (6' 3")	2.4 (8' 0")	1.9 (6' 3")	2.4 (8' 0")
Overall Length	5276 (207.7)	5834 (229.7)	5784 (227.7)	6342 (249.7)
Overall Height (empty)	1890 (74.4)/1946 (76.6)	1882 (74.1)/1930 (76.0)	1897 (74.7)/1946 (76.6)	1892 (74.5)/1940 (76.4)
Overall Cab Width ⁽¹⁾	2029 (79.9)	2029 (79.9)	2029 (79.9)	2029 (79.9)
Tailgate Load Height	837 (34.0)/897 (35.3)	859 (33.8)/892 (35.1)	856 (33.7)/892 (35.1)	853 (33.6)/889 (35.0)
Ground Clearance (empty) – Front Axle	211 (8.3)/231 (9.1)	211 (8.3)/234 (9.2)	211 (8.3)/241 (9.5)	211 (8.3)/234 (9.2)
– Rear Axle	206 (8.1)/203 (8.0)	203 (8.0)/203 (8.0)	206 (8.1)/203 (8.0)	206 (8.1)/203 (8.0)
Track – Front	1727 (68.0)	1727 (68.0)	1727 (68.0)	1727 (68.0)
– Rear	1712 (67.4)	1712 (67.4)	1712 (67.4)	1712 (67.4)
Overhang – Front	1001 (39.4)	1001 (39.4)	1001 (39.4)	1001 (39.4)
– Rear	1217 (47.9)	1267 (49.9)	1217 (47.9)	1267 (49.9)
Back of Cab to Rear Bumper	2154 (84.8)	2713 (106.8)	2154 (84.8)	2713 (106.8)
Front Bumper to Back of Cab	3123 (123.0)	3123 (123.0)	3632 (143.0)	3632 (143.0)
Approach Angle (degrees)	16.3/20.0	16.5/20.1	16.5/20.1	16.7/20.2
Breakover Angle (degrees)	23.1/21.5	21.1/17.8	21.1/17.8	19.8/15.7
Departure Angle (degrees)	25.2/26.9	24.1/25.7	25.0/26.7	23.9/25.5

*All dimensions are in mm (in.) unless noted. ⁽¹⁾Not including mirrors.

EXTERIOR DIMENSIONS*	REGULAR CAB 4x2/4x4		QUAD CAB® 4x2/4x4			
	2500	3500	2500		3500	
	Long Box	Long Box	Short Box	Long Box	Short Box (SRW)	Long Box ⁽¹⁾
Wheelbase	3569 (140.5)	3569 (140.5)	3569 (140.5)	4077 (160.5)	3569 (140.5)	4077 (160.5)
Box Length – m (ft. in.)	2.4 (8' 0")	2.4 (8' 0")	1.9 (6' 3")	2.4 (8' 0")	1.9 (6' 3")	2.4 (8' 0")
Overall Height (empty)	1875 (73.8)/1981 (78.0)	1897 (74.7)/1999 (78.7)	1890 (74.4)/1994 (78.5)	1890 (74.4)/1994 (78.5)	1905 (75.0)/2011 (79.2)	1905 (75.0)/2009 (79.1)
Overall Cab Width ⁽²⁾	2029 (79.9)	2029 (79.9)	2029 (79.9)	2029 (79.9)	2029 (79.9)	2029 (79.9)
Tailgate Load Height	838 (33.0)/917 (36.1)	853 (33.6)/945 (37.2)	838 (33.0)/917 (36.1)	846 (33.3)/917 (36.1)	853 (33.6)/942 (37.1)	864 (34.0)/942 (37.1)
Ground Clearance (empty) – Front Axle	208 (8.2)/236 (9.3)	226 (8.9)/251 (9.9)	210 (8.3)/236 (9.3)	210 (8.3)/236 (9.3)	226 (8.9)/251 (9.9)	226 (8.9)/251 (9.9)
– Rear Axle	203 (8.0)/201 (7.9)	218 (8.6)/216 (8.5)	203 (8.0)/201 (7.9)	203 (8.0)/201 (7.9)	218 (8.6)/216 (8.5)	218 (8.6)/216 (8.5)
Track – Front	1763 (69.4)/1770 (69.7)	1763 (69.4)/1770 (69.7)	1763 (69.4)/1770 (69.7)	1763 (69.4)/1770 (69.7)	1763 (69.4)/1770 (69.7)	1763 (69.4)/1770 (69.7)
– Rear	1732 (68.2)/1732 (68.2)	1925 (75.8)/1925 (75.8)	1732 (68.2)/1732 (68.2)	1732 (68.2)/1732 (68.2)	1732 (68.2)/1732 (68.2)	1925 (75.8)/1925 (75.8) ⁽³⁾
Overhang – Front	1001 (39.4)	1001 (39.4)	1001 (39.4)	1001 (39.4)	1001 (39.4)	1001 (39.4)
– Rear	1267 (49.9)	1267 (49.9)	1217 (47.9)	1267 (49.9)	1217 (47.9)	1267 (49.9)
Back of Cab to Rear Bumper	2713 (106.8)	2713 (106.8)	2154 (84.8)	2713 (106.8)	2154 (84.8)	2713 (106.8)
Front Bumper to Back of Cab	3124 (123.0)	3124 (123.0)	3632 (143.0)	3632 (143.0)	3632 (143.0)	3632 (143.0)
Approach Angle (degrees)	16.6/24.3	17.5/25.2	16.6/24.3	16.6/24.4	17.5/25.2	17.6/25.3
Breakover Angle (degrees)	20.7/21.0	21.8/22.2	20.7/21.0	19.5/18.7	21.8/22.2	20.6/19.8
Departure Angle (degrees)	23.3/26.8	24.0/27.9	24.3/27.9	23.6/26.7	25.0/29.1	24.3/27.9

*All dimensions are in mm (in.) unless noted. ⁽¹⁾3500 with Dual Rear Wheels shown. ⁽²⁾Not including mirrors. Overall width with Dual Rear Wheel long box is 2438 (96.0). ⁽³⁾1732/(68.2)/1732/(68.2) on Single Rear Wheel models. SRW – Single Rear Wheel

INTERIOR DIMENSIONS*	Regular Cab	Quad Cab®	
	Front	Front	Rear
Headroom	1039 (40.9)	1036 (40.8)	1016 (40.0)
Legroom	1041 (41.0)	1041 (41.0)	1039 (36.7)
Shoulder Room	1702 (67.0)	1702 (67.0)	1694 (66.7)
Hiproom	1648 (64.9)	1646 (64.8)	1646 (64.8)
Front Seat Adjustment (fore and aft)	229 (9.0)	229 (9.0)	–
Interior Volume – L (cu. ft.)	1843 (65.1)	1838 (64.9)	1606 (56.7)

*All dimensions are in mm (in.) unless noted.

Specifications, descriptions and illustrative material contained herein are based on authorized information. Although specifications, descriptions and illustrations were believed to be correct at the time this publication was approved for printing, accuracy cannot be guaranteed. DaimlerChrysler Canada Inc. reserves the right to discontinue models or options at any time or change specifications and materials, equipment or design without notice and without incurring obligation. Some equipment may not be exactly as illustrated in this publication. Some of the equipment listed, described, or illustrated herein may not be standard, and may be available only at extra cost, as factory-installed or retailer-installed; items described as "available" may be standard on some models and optional, or not available, on others. Equipment referred to as "available" or "optional" may be at extra cost. Some options are required in combination with other options. For the price of the model with the equipment you desire or verification of specifications and equipment availability contained herein, see your Chrysler, Jeep®, Dodge retailer.

HEMI, Magnum and Quad Cab are registered trademarks of DaimlerChrysler Corporation. Sentry Key is a trademark of DaimlerChrysler Corporation. HomeLink is a registered trademark of Johnson Controls Technology Company. Infinity is a registered trademark of Harman International Industries, Inc. Preferred Suede is a trademark of Milliken & Company. Cummins is a registered trademark of Cummins Engine Company, Inc.

©2003 DaimlerChrysler Canada Inc. All rights reserved.

BOX DIMENSIONS*	Short Box	Long Box
Box Length m (ft. in.)	1.9 (6' 3")	2.4 (8' 0")
Number of Stake Pockets (per-side)	2	3
Maximum Length at Floor	1928 (75.9)	2487 (97.9)
Overall Length of Box	2047 (80.6)	2606 (102.6)
Front of Box to End of Open Tailgate	2540 (100.0)	3099 (122.0)
Open Tailgate	490 (19.3)	490 (19.3)
Depth of Box	512 (20.2)	512 (20.2)
Cargo Volume – L (cu. ft.)	1634 (57.7)	2093 (73.9)
Width Between Wheelhouse	1295 (51.0)	1295 (51.0)
Maximum Cargo Width at Floor	1686 (66.4)	1686 (66.4)
Tailgate Opening	1612 (63.5)	1612 (63.5)

*All dimensions are in mm (in.) unless noted.

Colour availability may vary by model. Due to printing limitations, the colours shown here and throughout this catalogue may vary slightly from the actual hue. See your retailer for model applications and to view accurate colour chips.